

Maxi Brute Six Light 6000 watts




- Power: 1000W 6000W max
- Voltage: 100V-250V compatible
- Lamp socket: Mogul end prong PAR 64
- Power plug: CEE Norm 2P+E type 32 / 32A-6H 200V-250V
- Weight: 16 kg
- 6 toggle switches allow total control over light output
- Focusing and light output vary by bulb type

The Cinelight MaxiBrute Six-Light 6KW is mainly used for lighting large areas in television and film productions.

The high intensity output of this fixture allows a minimum number of units for the required lighting level.

<u>Key Features:</u>

- accepts different bulbs with built-in reflectors that disperse or intensify the light beam emitted from the heads
- pivoted three globe modules permit variable beam coverage
- six toggle switches allow total control over light output
- 100V-250V compatible
- power: 1000W 6000W max
- socket (lampholder): Mogul end prong PAR 64
- power plug type: 2P+E type 32 / 32A-6H 200V-250V
- focusing and light output vary by type of bulb use
- mounting: spigot 28mm pin



TUNGSTEN - FLOOD

Beam type	flood
Rated power	6000 watts
Voltage input	100-240V 50 / 60 Hz
Lamp type	PAR64
Lamp socket	GX16D
Color temperature	3200K
Beam angle	According to lamp model
Photometrics	According to lamp model
Yoke mount	Spigot 28mm pin
Housing color	Black
Housing material	Metal
Power connector type	CEE 2P+E
Power cord total length	7.0 m
Lamp head dimensions	98 x 62 x 24 cm
Lamp head weight	15 kg