



## FEATURES

LED chip : TYANSHINE  
12 pcs \*15 W RGBW 4  
in 1 LED chip

Zoom : 7 to 55 degree

IP rate : IP66

Built-in with color calibration system, which can sure the color mixing consistency

Compact , convenient for installation and delivery

Housing with high pressure engineering plastic, anti-UV, anti-high temperature and anti-aging.

### Parameters

## Light Source / Power System

Voltage : AC100-240V, 50/60Hz  
Power : 157W PF0.96  
LED chip : 12pcs×15W RGBW LED  
Lifespan : 30000h  
Lens material : PMMA

## Color / GOBO / Effects

Zoom angle : 7° ~ 55° Linear electric zoom  
Installation working angle : ±90  
Color Temperature : 2500K-10000K  
CRI : Ra≥75  
Color mixing : RGBW macro color system.  
Strobe : 1-30Hz electronic strobe and random strobe.  
Dimmer : 16Bit, 0 to 100% Linear electronic dimmer , provides four dimming options ;

## Control System

Control Mode : DMX512,RDM  
DMX Channels : 9 channel (standard) 5 channel (Simple)  
Intelligent temperature control : Display board can record device's using time , show device's temperature, channel data and software version .



## Other functions

Display : 0.9 Inches OLED display screen. With Chinese and English two version language.

Software upgrade : Upgrade via DMX connector

RDM : RDM signal two-way transmission

Thermal Dissipation : Passive ( fanless )

Ambient temperature : -20 ~ +40°C

## Appearance Parameters

Housing : Housing with high pressure engineering plastic, anti-UV, anti-high temperature and anti-aging.

IP rate : IP66

Light size : 334×242×432mm

N.W : 7.20Kg

Single Carton Packing : 330×330×475mm

N.W : 7.20Kg      G.W : 9.2 Kg

4 in 1 Carton Packing : 685×685×500mm

N.W : 28.4Kg      G.W : 37.2Kg

6 in 1 flycase Packing : 915×795×630mm

N.W : 43.2Kg      G.W : 82.5Kg