

SmallHD 702 Touch 7" On-Camera Monitor



The **SmallHD 702 Touch 7" On-Camera Monitor** features an IPS LCD panel with a resolution of 1920 x 1200. The IPS touchscreen provides a wide off-axis viewing experience without a significant shift in color or contrast. The panel also features a maximum brightness of 1500 cd/m², which makes it more than well suited for use outdoors. The panel displays images in 8-bits per color channel, but the monitor's internal processing is 10-bit. The touchscreen capability of the monitor facilitates using the SmallHD OS3 software package that allows you to create looks and save them as pages.

Interchangeable battery plates allow you to use the battery of your choice. However, the monitor ships with a dual L-series battery plate. The 702 Touch incorporates 3G-SDI and HDMI inputs and outputs, as well as a headphone jack for monitoring audio. It also has a store of monitoring features including waveform, custom LUT support, anamorphic de-squeeze, and audio meters.

Key Features

- 7" Daylight Viewable 1920 x 1200 Display
- 10-Bit Processing, 8-Bit Display
- 3G-SDI & HDMI Inputs/Outputs
- Headphone Jack
- Aircraft-Grade Aluminum Unibody
- 1500 cd/m² Brightness, 1000:1 Contrast
- Waveform, Custom LUTs, De-Squeeze & More
- Interchangeable Battery Plates
- 12 Switchable Pages of Favorite Features