

True Blue T5

ARRI True Blue® – Location, Studio and Theater Fresnels



ARRI True Blue represent an unprecedented evolution of the location fixtures that have been popular workhorses for over two decades. Following extensive research and feedback from lighting professionals around the world, combined with advances in technology, ARRI has designed a series of six highly innovative lampheads with over 30 new improvements for studio and location lighting. ARRI True Blue T5 is available in both manual and pole-operated versions.

Features



Cross-Cooling System: new, highly effective cooling streams in addition to conventional cooling

Sliding Stirrup: centre of gravity adjustment

Tilt Lock: stainless steel friction disc for rigid lock-off

Top Latches: application-oriented Top Latches for location or studio use

Adjustable Accessory Brackets: adjustable 2-scrim and 4-scrim position

Stainless Steel Lens Protection: maximised light transmission and high temperature stability

Extremely Robust Barndoors: made of special alloy with high strength-to-weight ratio and effective tightening function

Maintenance: more shared parts, very fast access to all interior workings with three torx drivers only

Protection Rating IP23: safe indoor and outdoor use

Safety Certification: CE, CB, GS, cNRTLus

Technical Data

Category

Tungsten

Series

True Blue T

Model

True Blue T5

Mains Plug

Bare Ends

Lamphead Type

Fresnel, 5,000 W

Reflector

Spherical specular high purity aluminium

Power Consumption	5,000 W
Voltage Range	230 V / 120 V
Lamp Base	G38
Dimming	yes, 0 to 100 % via external dimming system
Correlated Color Temperature	3,200 K
Beam Angle	10° to 54°
Weight in kg net*	approx. 12 kg
Weight in kg packed*	approx. 17 kg
Weight in lbs. net*	approx. 26 lbs
Weight in lbs. Packed*	approx. 37 lbs
Measurements (HxWxL) incl. Pin in mm*	655 x 465 x 390 mm
Measurements (HxWxL) excl. Pin in mm*	522 x 465 x 390 mm

Measurements (HxWxL) incl. Pin in inch*	25,8 x 18,3 x 15,4"
Measurements (HxWxL) excl. Pin in inch*	20.6 x 18.3 x 15.4"
Measurements (HxWxL) Packed size in mm*	495 x 510 x 555 mm
Measurements (HxWxL) Packed size in inch*	12.5 x 20.1 x 21.9"
Lens / UV-Protection Glass Diameter in mm	250 mm
Lens / UV-Protection Glass Diameter in inch	9.8"
Accessory Diameter in mm	330 mm
Accessory Diameter in inch	13.0" (Scrim)
Barndoor in mm	344 mm
Barndoor in inch	13.5"
Mounting	Spigot 28 mm / 1 1/8" (1.1")
Housing Color	Blue/Silver, Black



Protection Class / IP Rating

I / IP23

Certifications

CE, CB, ENEC, cNRTLus